



Florida Pedestrian Planning and Design Handbook



Florida Pedestrian Planning and Design Handbook

Prepared for:

Florida Department of Transportation

By:

**University of North Carolina
Highway Safety Research Center**

April 1999

Table of Contents

| | |
|-------------------------------------------------------------------------------------------------------|-----------|
| Preface | i |
| Chapter 1-Walking: the World's First and Foremost Choice in Motion | 1 |
| Challenges to Walking | 2 |
| A Renewed Interest in Walking | 3 |
| The Psychology of Space | 4 |
| About the Manual | 5 |
| Appendix | 7 |
| References | 7 |
| Chapter 2-Planning For Pedestrians | 9 |
| The FDOT Pedestrian/Bicycle Program | 10 |
| Local Initiatives | 10 |
| Public Involvement | 10 |
| The Pedestrian Planning Process | 11 |
| Transportation Equity Act for the 21st Century (TEA-21) Funding Sources for Pedestrian Projects | 13 |
| Major Sources of Funding at the State Level | 13 |
| Sources of Local Funds | 14 |
| Ongoing Evaluation | 15 |
| References | 15 |
| Chapter 3-Human Factors and the Pedestrian | 17 |
| Visibility and Detection | 17 |
| Motorist Behavior | 20 |
| Traffic Engineering Practices | 21 |
| Pedestrian Behavior | 22 |
| Pedestrian Capacities | 24 |
| References | 27 |
| Chapter 4-Characteristics of Pedestrian- Motor Vehicle Crashes in Florida | 29 |
| Pedestrian Actions and Crash Types | 29 |
| Fatalities and Injuries by Age | 35 |
| Light Condition | 36 |
| Alcohol and Drug Use Among Pedestrians | 39 |
| References | 39 |
| Chapter 5-Pedestrians with Disabilities | 41 |
| The Americans with Disabilities Act (ADA) | 42 |
| Resources | 46 |
| Chapter 6-Sidewalks, Walkways, and Paths | 49 |
| Placement | 50 |
| Design Elements | 51 |
| Recommended Minimum Effective Width | 52 |
| Maintenance | 54 |

| | |
|---------------------------------------------------------------------------------------------|------------|
| References | 54 |
| Chapter 7-Motorist & Pedestrian Signs & Markings | 57 |
| Regulatory Signs | 57 |
| Warning Signs | 60 |
| Pavement Markings | 62 |
| Pavement Messages for Pedestrians | 62 |
| Voice Messages for Pedestrians | 62 |
| References | 62 |
| Chapter 8-Signalization | 65 |
| Signal Warrants | 65 |
| Pedestrian Signals | 66 |
| References | 73 |
| Chapter 9-Crosswalks, Stop Lines, Curb Ramps, and Refuge Islands | 75 |
| Crosswalks | 75 |
| Stop Lines | 81 |
| Curb Ramps | 84 |
| Refuge Islands and Medians | 85 |
| References | 87 |
| Chapter 10-One-way Streets | 89 |
| Advantages of One-way Streets | 89 |
| Disadvantages of One-way Streets | 90 |
| References | 91 |
| Chapter 11-Intersections | 93 |
| Discussion | 93 |
| Recommendations | 94 |
| References | 99 |
| Chapter 12-Midblock Crossings | 101 |
| Medians and Refuge Islands — Powerful Safety Tools | 101 |
| Midblock Crossings by Roadway Classification | 105 |
| Midblock Crossing Design | 107 |
| Midblock Signals | 108 |
| The Placement and Design of Driveways | 108 |
| Chapter 13-Parking and Safe Access to Buildings and Schools | 111 |
| Discussion | 111 |
| Site Planning | 112 |
| Recommendations | 113 |
| Simplify and Calm Motor Vehicle Movement to Promote Pedestrian Safety in Parking Lots | 114 |
| References | 117 |

| | |
|-----------------------------------------------------------------|------------|
| Chapter 14-School Access and School Zone Practices | 119 |
| School Safety Program | 119 |
| School Location and On-Site Safety | 120 |
| School Operating Plan | 121 |
| Traffic Controls in School Zones | 121 |
| School Crossing Guards | 122 |
| Crossing Guard Training..... | 124 |
| School Safety Patrol | 124 |
| References | 125 |
| | |
| Chapter 15-Traffic Calming Strategies | 127 |
| Introduction | 127 |
| What Is Traffic Calming? | 127 |
| Controls Involving Traffic Diversion..... | 133 |
| Managing Traffic in Place | 135 |
| The Planning Process..... | 139 |
| References | 140 |
| Bibliography | 141 |
| | |
| Chapter 16-Exclusive Pedestrian Facilities | 143 |
| Planning Considerations | 143 |
| Design Considerations | 146 |
| Implementation Considerations | 147 |
| Summary | 148 |
| Bibliography | 148 |
| | |
| Chapter 17-Work Zone Pedestrian Safety | 151 |
| References | 153 |
| Bibliography | 153 |
| | |
| Chapter 18-On-Street Parking | 155 |
| Urban Area Characteristics | 156 |
| Sight Distance and Parking Restrictions | 160 |
| References | 161 |
| | |
| Chapter 19-Street Lighting For Pedestrians | 163 |
| Lighting for Other Pedestrian Facilities..... | 164 |
| References | 165 |
| Bibliography | 165 |
| | |
| Chapter 20-Grade-Separated Crossings | 167 |
| Types of Facilities | 167 |
| Planning Considerations | 168 |
| Pedestrian Transportation | 171 |
| References | 173 |
| | |
| Chapter 21-Boulevards..... | 175 |
| What is a Boulevard?..... | 175 |
| Why Are Boulevards Better than the Alternative? | 176 |
| Esplanade — Chico, California | 176 |

| | |
|-----------------------------------------------------------------------|------------|
| Comparisons Between Boulevards | 177 |
| What Designs Are Most Safe? | 177 |
| Intersections | 177 |
| Access Lanes | 178 |
| Boulevards Work Best When the Pedestrian Is an Equal | 178 |
| Conclusion | 179 |
| References | 179 |
| Appendix A- Traffic Laws and Definitions for Pedestrians | 181 |
| Design/Law Link | 181 |
| Jaywalking | 181 |

List of Tables

| | |
|------------------------------------------------------------------------------|-----|
| Table 8-1. Warrants for installing new traffic signals. | 66 |
| Table 9-1. Recommended guidelines for crosswalk design and placement.4 | 77 |
| Table 20-1. Pedestrian facility evaluation variables.2 | 171 |
| Table 20-2. Major cost components of pedestrian facilities.2 | 173 |

List of Figures

| | |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|
| Figure P-1. Everything starts with the street. The Florida Department of Transportation and Ft. Lauderdale made State Route A-1-A a commercial success. The street design was improved by widening sidewalks, dropping lanes, adding bike lanes as buffers, and landscaping. | ii |
| Figure P-2. In order to retain the best people, large corporations are realizing that they need towns, neighborhoods, and shopping districts where people find security, convenience, efficiency, comfort, and a sense of welcome. These qualities are achieved by well-designed pedestrian oriented streets. | ii |
| Figure 1-2. Along many streets, sidewalks are either discontinuous or nonexistent. | 3 |
| Figure 1-3. The fear of getting hit by a motor vehicle is a concern to most pedestrians. | |
| Figure 1-4. Major commercial strips are often inhospitable to pedestrians. | |
| Figure 1-5. An attractive street invites low speeds in Meisner Park, Boca Raton. | 5 |
| Figure 2-1 The Florida Pedestrian Safety Plan covers planning, engineering, education, enforcement, and implementation. | 10 |
| Figure 2-2 The public often brings a broad perspective to the development of plans and projects for the community. | 11 |
| Figure 2-3. Focus groups provide information on needs and opportunities in the community. | 12 |
| Figure 2-4. School children and the elderly are two pedestrian target groups. | 14 |
| Figure 3-1. On higher speed urban roads, low-level tungsten lights on high-angle cobra mounts provide even lighting to the entire roadway. | 19 |
| Figure 3-2. Diagonal spans (above) are not encouraged, because motorists are looking into the sky far from the opposing traffic and the pedestrian. Instead, left emphasis enhancement signals are encouraged (right), because they allow motorists to observe the signal, oncoming traffic, and the pedestrian at the same time. | 22 |
| Figure 3-3. When practical, signal cycles should be timed so that pedestrians do not have to wait longer than 30 seconds. | 23 |

| | | |
|--------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|
| Figure 3-4. | Signal timing should be set for the special populations that use a particular crossing. | 24 |
| Fig. 3-5. | School crossing guards help children to cross streets safely. | 25 |
| Figure 3-6. | Fifty-five percent of older males have hearing problems and are subject to right turning conflicts. | 26 |
| Figure 4-1. | Pedestrians killed in Florida, 1980-1997. | 30 |
| Figure 4-2. | Pedestrian fatality rates in Florida and the United States, 1980-1995. | 30 |
| Figure 4-3. | Actions of pedestrians killed in Florida, 1988-1992. | 31 |
| Figure 4-4 | Pedestrian accident types (continued on next page). | 31 |
| Figure 4-4 | continued. Pedestrian accident types. | 32 |
| Figure 4-6. | Major pedestrian crash type subgroups in Florida, 1991. | 33 |
| Figure 4-5. | Intersection dash accidents are the most common accident type for 5- to 9-year-old children, particularly males. | 33 |
| Figure 4-7. | Florida pedestrian fatalities and injuries by age, 1988-1992. | 34 |
| Figure 4-8. | Age of pedestrians involved in crashes, six-state study, 1991 data. | 34 |
| Figure 4-9. | Pedestrian crash types by age, six-state study, 1991 data. | 35 |
| Figure 4-10. | Florida pedestrian fatalities by light condition, 1993-1997. | 36 |
| Figure 4-11. | Pedestrian fatalities by light condition and age, six-state study, 1991 data. | 37 |
| Figure 4-12. | Pedestrian crashes by light condition, six-state study, 1991 data. | 37 |
| Figure 4-13. | Florida pedestrian fatalities by impairment, 1993-1997. | 38 |
| Figure 4-14. | Pedestrian crash types by impairment, six-state study, 1991 data. | 38 |
| Figure 4-15. | Pedestrians who drink have the judgment skills of a child and the mobility skills of a senior. | 39 |
| Figure 5-1. | Pedestrian facilities must be designed to accommodate the needs of the physically disabled. | 42 |
| Figure 5-2. | Curb cuts are the single most important design consideration for persons in wheelchairs. | 43 |
| Figure 5-3. | A pavement grinding project left an exaggerated lip at this curb cut. | 44 |
| Figure 5-4. | This island (above and left) does not have a cut-through. Note that the older woman is having difficulty whereas the other pedestrians (left) are already crossing. | 45 |
| Figure 6-1. | Properly built sidewalks are essential for increasing pedestrian comfort, mobility, accessibility, and safety. | 50 |
| Figure 6-2. | Recommended minimum effective sidewalk widths based on area type, roadway type, and number of dwelling units per acre. ⁵ | 52 |
| Figure 6-3. | Sidewalks should be properly maintained, free from obstructions and potential problems for pedestrians. | 54 |
| Figure 6-4. | A wide setback distance increases pedestrian comfort. | 53 |
| Figure 7-1. | Typical regulatory signs relating to pedestrians. | 58 |
| Figure 7-2. | Typical warning signs relating to pedestrians. | 60 |
| Figure 7-3. | Pedestrian crossing signs along the edge of the roadway may be supplemented by signs in | |

| | |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|
| the median, overhead signs, and high-visibility crosswalk markings. | 61 |
| Figure 8-1. Pedestrian signal displays. | 67 |
| Figure 8-2. Crosswalks, traffic signals, and pedestrian signals give pedestrians the opportunity to cross streets predictably and effectively. | 68 |
| Figure 8-3. Example of an instructional sign for pedestrians to activate the signal. | 68 |
| Figure 8-4. Example of an educational sign for pedestrian signal displays. | 69 |
| Figure 8-5. Pedestrian push button and signal heads are placed in channelized islands to guide pedestrians over a shorter crossing distance. | 70 |
| Figure 8-6. Right-turn-on-red restrictions can improve pedestrian safety when used properly. The top sign creates confusion and should not be used. The bottom sign conveys a much clearer message. | 71 |
| Figure 9-1. Properly designed crosswalks, curb ramps, and refuge islands can greatly enhance a pedestrian's ability to cross a street. | 76 |
| Figure 9-2. Guidelines for crosswalk installation at uncontrolled intersections and midblock crossings. | 78 |
| Figure 9-3. A crosswalk at a skewed intersection — there is a trade-off between making a 90-degree turn and staying close to the turning traffic. | 79 |
| Figure 9-4. Typical crosswalk markings. | 80 |
| Figure 9-5. High-visibility markings such as longitudinal lines may be used in crosswalks for increased emphasis. | 81 |
| Figure 9-6. Crosswalk placement in accordance with various ramp designs. (A) and (b) are the preferred treatments in Florida. (C) and (d) should be used only if there are right-of-way constraints or if significant retrofitting of drainage facilities would be required. | 82 |
| Figure 9-7. The failure to use stop lines encourages many motorists to stop too close to the intersection, forcing pedestrians into the parallel roadway. A midblock stop line queues motorists back 40 feet, reducing the chance for a multiple threat crash. | 83 |
| Figure 9-8. Side treatments for curb ramps. | 84 |
| Figure 9-9. A tactile curb ramp. | 85 |
| Figure 9-10. Refuge islands allow pedestrians to cross one direction of traffic, rest if necessary, and then cross the other direction of traffic. | 86 |
| Figure 10-1. One-way streets offer a number of advantages for pedestrians. | 90 |
| Figure 10-2. One-way streets that contain wide travel lanes can result in higher than desired vehicle speeds, which can cause problems for pedestrians. | 91 |
| Figure 11-1. Traffic engineers face their greatest dilemma at the intersection. | 94 |
| Figure 11-2. Medians are recommended whenever the crossing distance exceeds 60 feet to provide a refuge for pedestrians. | 95 |
| Figure 11-3. Signals frequently used by elderly or physically impaired pedestrians should be retimed to provide a crossing time commensurate with their ability. | 96 |
| Figure 11-4. This intersection could be improved in many ways. Note that pedestrians leaving the lower right corner must walk a distance of over 20 feet just to get to the first lane to be crossed—a channelized slip lane would reduce this distance. | 96 |
| Figure 11-5. Modern roundabouts can reduce vehicle speed and pedestrian/vehicle conflicts. | 97 |

| | |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| Figure 11-6. Right-turn slip lanes, where the right-turning traffic must yield before entering the roadway, are a safer alternative for pedestrians than double right-turn lanes. | 98 |
| Figure 11-7. AASHTO's standards for right-turn slip lanes (left) encourage high motor vehicle speeds and provide low visibility. By comparison, FDOT's recommended standards encourage low motor vehicle speeds and provide good visibility. | 99 |
| Figure 12-1. Midblock crossing without median—the person must look in both directions. | 103 |
| Figure 12-2. Midblock crossing with median — the pedestrian needs to look in only one direction at a time. | 103 |
| Figure 12-3. AASHTO's standards for right-turn slip lanes (left) encourage high motor vehicle speeds and provide low visibility. By comparison, FDOT's recommended standards encourage low motor vehicle speeds and provide good visibility. | 104 |
| Figure 12-4. A raised median provides median provides pedestrians a place to wait safely and to cross one directions of traffic at a time. | 105 |
| Figure 12-5. At times it may be necessary to block midblock access to pedestrians, such as on this busy section of U.S. Route 1 through Miami. These shrubs below the palm trees are dense enough to divert pedestrians to adjacent intersections. | 106 |
| Figure 12-6. At this midblock crossing in Venice, Florida, the motorist and pedestrian can see one another. | 107 |
| Figure 13-1. Pedestrians need safe and attractive entrances with walkways that do not conflict with vehicle traffic. | 112 |
| Figure 13-2. Pedestrian oriented designs such as this one minimize pedestrian conflicts with autos, creating a safe area to shop and relax. | 112 |
| Figure 13-3. This “herring bone” parking lot design is impractical for pedestrians to navigate. | 113 |
| Figure 13-4. If a walkway does not provide the most direct route, it will not be used often. | 114 |
| Figure 13-5. This effective treatment allows pedestrians safe, convenient access to this building from the sidewalk even while traversing a parking lot. | 114 |
| Figure 13-6. Unrestricted driveway access creates eight potential conflict points at every driveway (left). A raised median and consolidating driveways reduce conflict points (below left). | 115 |
| Figure 13-7. Bulbouts (or corner flares) shorten pedestrian crossings distances and slow traffic speeds. | 116 |
| Figure 13-9. Informational signs and maps help tourists immensely in some situations. | 117 |
| Figure 13-8. Enhanced pedestrian crossings assist the designer where pedestrian traffic and movements are dominant or preferred. | 117 |
| Figure 14-1. Properly designed facilities in school zones are necessary to create a safe environment for children. | 120 |
| Figure 14-2. Example of school site layout. | 121 |
| Figure 14-3. Warning signs used to alert motorists to schools and school crossings. | 122 |
| Figure 14-4. Crossing guards should not simply hold up a sign and let the children run across the street. Scenes such as this one prove the need for a crossing guard training program. | 123 |
| Figure 15-1. These medians and bulbouts calm traffic on this revitalized main street. | 128 |
| Figure 15-2. Traffic calming—advantages and disadvantages. | 129 |

| | |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| Figure 15-3. Traffic control measures used to manage traffic in place. | 134 |
| Figure 15-4. A traffic mini-circle used at the intersection of residential streets. | 136 |
| Figure 15-5. A choker (curb bulb) used on a one-way residential street. | 137 |
| Figure 15-6. Speed humps are intended to reduce traffic speeds to 32 to 40 km (20 to 25 miles) per hour. | 138 |
| Figure 16-1. Pedestrian malls provide for pedestrian safety and mobility. | 145 |
| Figure 16-2. Crosswalks should be provided for pedestrians to cross streets in interrupted malls. | 146 |
| Figure 16-3. Pedestrian malls enhance the aesthetics of the downtown area. | 147 |
| Figure 17-1. Two approaches to accommodate pedestrians in a midblock workzone. | 152 |
| Figure 18-1. On-street parking in commercial areas provides convenient parking and minimizes the negative impacts of off-street parking. | 156 |
| Figure 18-2. Pedestrian sight distance and parking restriction for a parallel-parked vehicle, pedestrian standing at the curb. | 157 |
| Figure 18-3. Pedestrian sight distance and parking restrictions — for a parallel-parked vehicle, pedestrian standing halfway into the parking lane. | 157 |
| Figure 18-4. Pedestrian sight distance and parking restrictions—angle parking at 90 degrees. | 158 |
| Figure 18-5. Pedestrian sight distance and parking restrictions — angle parking at less than 90 degrees. | 159 |
| Figure 19-1. Street lights improve pedestrian operations and security. | 164 |
| Figure 20-1. Grade-separated crossings improve pedestrian safety. | 168 |